

SF-NVR8232A-B2

Safire Smart

NVR recorder for IP cameras B2

range

32CH video / Compression H.265S /

2HDD

Resolution up to 12Mpx / Bandwidth

192Mbps

2 HDMI and VGA / Dewarping

Fisheye

Facial recognition, Video metadata



Safire Smart

B2

NVR for IP cameras

32 CH

192 Mbps bandwidth supported

Maximum resolution 12 Megapixel

Compression H.265S/H.265+/H.265/H.264+

1 HDMI output 4K, HDMI FullHD output and 1 VGA output

POS Function

Intelligent searches of humans, vehicles and two-wheelers

Facial recognition

Face tracking on map

Dewarping for Fisheye cameras

Arming / Disarming from the mobile APP

IP Dual Stream Access

RCA Audio

Alarms

Space for 2 HDD

WEB, CMS and Smartphone interface

ONVIF Compatible

NDAA Certificate

Specifications

Brand	Safire Smart
Range	B2
Inputs for IP cameras	32CH IP
IP compatible cameras	Safire Smart (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Main Stream recording	12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/ 960H/D1/CIF
Decoding capacity	1CH 12Mpx @ 20FPS 4CH 1080P @ 30FPS
Video compression format	H.265+ / H.265 / H.264+ / H.264
Audio Compression	G.711(U/A)
Total bandwidth	160 Mbps downstream / 160 Mbps upstream
Video outputs	1 HDMI 4K / 1 HDMI FullHD / 1 VGA
Display resolution	HDMI 1: 3840x2160, 1920x1080, 1280x1024, 1024x768 HDMI 2: 1920x1080, 1280x1024, 1024x768 VGA: 1920x1080, 1280x1024, 1024x768 *HDMI 1 and HDMI 2 separate *HDMI 1 and VGA simultaneous
Yesmultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Multi-Screen	Main output: 1 / 4 / 6 / 8 / 9 / 13 / 16 / 25 / 36 (Live View) Secondary output: 1 / 4 / 6 / 8 / 9 (Live view)
Recording method	Manual, programmed, motion detection, smart events, alarm input, POS
POS Function	Si
Perimeter Protection	Need to use Safire Smart 4I1 or 8I2 cameras Artificial Intelligence based on the classification of humans, vehicles and two-wheeled vehicles on: - Area intrusion - Line crossover - Region entry - Exit region
Facial recognition	Detailed searches for intelligent events Face detection with Safire Smart cameras 4I1 or 8I2 up to 32CH (All channels) Face detection by the NVR itself with any camera up to 2CH Facial recognition up to 6CH max Computation of up to 18 images / second 32 Libraries and up to 10000 face images
Video metadata	Image searches via recorder, APP and PC software Face tracking on map or plan Statistical information on face results by day, week, month or customized period Need to use Safire Smart 4I1 or 8I2 cameras Human and vehicle feature extraction For humans: Can extract up to 13 features (glasses, color of clothes, etc.) For vehicles: can extract up to 5características (color, type, etc.)
License plate recognition	Yes (Safire Smart license plate camera required)
Dewarping	Supports Fisheye camera dewarping via web and APP
Alarms	16 Inputs / 4 Outputs
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2x 3.5" HDD SATA3.0 up to 10 TB (not included)
Communication	1 x USB 3.0 / 2 x USB 2.0 / 2 x RJ45 10/100/1000M (Ethernet) / RS485
Remote access	Web Browser, Safire Smartphone App and PC Software Safire Smart VMS
Power	DC 12V / 4A, ? 20W (Without hard disk)
Operating temperature	-10°C ~50°C, Humidity 10~90%
Dimensions / Weight	48.1 (H) x 380 (W) x 268 (D) mm / 1.18 Kg