

SF-IPT010CA-4B1

Safire Smart

Turret IP camera range B1 Night

Color

Resolution 4 Megapixel (2560x1440)

Lens 2.8 mm | Built-in microphone

White LED range 20 m | PoE

(IEEE802.3af)

Waterproof IP67



Safire Smart

Range B1 with Night Color

Turret IP Camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8 mm Lens

Night Color, color image 24/7

White LED range 20 m

Compression H.265+ / H.264+

DWDR

3DNR

Integrated microphone

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 with Night Colour
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	Color: 0.03 Lux @(F1.6, AGC ON)
White LED range	20 m
Day/Night	Night Color, color image 24/h
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 3Mpx, 1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265+, H.265, H.264+, H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 95.5°, V: 52°, D: 112.3°
Range performance	59 m (D), 24 m (O), 12 m (R), 6 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, ROI, Mirror function, Privacy masking, ROI
Motion Detection	Yes
Smart Features	VCA Rules: Area intrusion, Line crossing, abandoned object, removed object, Video exceptions (scene change, video loss),
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 458 mA / 5.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Plastic
Temp. operation	-20° C ~ +55° C
Dimensions	73.70 (H) x 74.70 (W) x 161.5 (D) mm
Weight	240 g