

SF-IPB070CA-2B1

Safire Smart

Bullet IP Camera B1 range Night

Color

Resolution 2 Megapixel (1920x1080)

Lens 2.8 mm | Built-in microphone

White LED range 20 m | PoE

(IEEE802.3af)

Waterproof IP67



Safire Smart

Range B1 with Night Color

Bullet IP camera

1/3" Progressive Scan CMOS

2 Megapixel (1920x1080)

2.8 mm Lens

Night Color, color image 24/7

White LED range 20 m

Compression H.265+ / H.264+

DWDR

3DNR

Integrated microphone

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 with Night Colour
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	Color: 0.0462 Lux @(F2.2, AGC ON)
White LED range	20 m
Day/Night	Night Color, color image 24/h
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	25 FPS (1080P, 720P)
Extra Stream rate	25 FPS (D1, VGA, CIF, 480x240)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265+, H.265, H.264+, H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 87°, V: 48°, D: 103°
Range performance	49 m (D), 19 m (O), 8 m (R), 5 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, ROI, Mirror function, Privacy masking, ROI
Motion Detection	Yes
Smart Features	VCA Rules: Area intrusion, Line crossing, abandoned object, removed object, Video exceptions (scene change, video loss),
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 458 mA / 5.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Plastic
Temp. operation	-20° C ~ +55° C
Dimensions	73.70 (H) x 74.70 (W) x 161.5 (D) mm
Weight	240 g