

SF-IPB070-4B1

Safire Smart

Bullet IP camera B1 range

Resolution 4 Megapixel (2566x1440)

2.8 mm Lens

IR range 20 m | PoE (IEEE802.3af) m

Waterproof IP67



Safire Smart

B1

Bullet IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8 mm Lens

0 Lux

IR Range 20 m

Compression H.265 / H.264

DWDR

3DNR

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	Colour: 0.03 Lux @(F1.6, AGC ON), 0 Lux with IR
IR range	20 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 3Mpx, 1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265 / H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 98°, V: 53°, D: 116°
Range performance	56 m (D), 22 m (O), 11 m (R), 5 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, ROI, Mirror function, Privacy masking, ROI
Motion Detection	Yes
Smart Features	Area intrusion, Line crossing, abandoned object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	No
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 292 mA / 3.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-20° C ~ +55° C
Dimensions	73.70 (H) x 74.70 (W) x 161.5 (D) mm
Weight	270 g