


SAFIRE LIFEPO LITIUMBATTERI 1280WH RS-485 KOMMUNIKASJON IP67



Utgangsspenning (volt): 12VUtgangsstrøm (ampere): 10A

 Nominell kapasitet (AH/WHA/MAH): 1280wh

• DIN: Nei



Safire - Lithium LiFePo Battery 1280Wh (100Ah) - Integrated MPPT regulator - RS-485 for communication - Can connect to SF-SOLARPANEL-200W

- Safire
- MPPT with integrated battery
- Compatible with Safire solar panel of 200W
- 1280Wh LiFePo battery with 2000 charge and discharge cycles
- Integrated MPPT regulator
- Maximum supported load 20W
- Communication RS485 for third-party integration
- Degree of protection IP67

Brand Safire Material LiFePo

Capacity 100Ah (1280Wh)

Communication RS485 (For integration with third parties).

Provides all system information such as

load level, system status or power

consumption

Nominal voltage 12.8V Integrated DC Regulator (with

standard jack connector compatible with

CCTV cameras)

Operating temperature Charge: 0 °C to 65 °C (32 °F to 140 °F)

Discharge: -30 °C to 65 °C (-22 °F to 140

°F)

Cycles >2000

Maximum input power Up to 450W in total

Load voltage9~12.6VMaximum current load10AMaximum load supported20W

Regulator Integrated MPPT

Installation Can be coupled to the solar panel SF-SOLARPANEL-100W or stand alone

In mast between 100-200 mm

Degree of protection IP67

Installation bracket

Battery size 205 (W) x 68 (H) x 112 (D) mm